



SEMI SUB KANTAN 4



General				
Name	KANTAN 4	BOP Equipment		
Rig Type	A1 Column-stabilized Drilling Unit	BOP Stacks	1 x NOV Shaffer 5000psi 18-3/4" annular preventer	
	HELDK		1 x NOV Shaffer 10000psi 18-3/4" annular preventer	
Year of build	1983		2 x NOV Shaffer 15000psi 18-3/4" dual SLX	
Registry	Panama	Power Equipment		
Classification	ABS	Diesel Engines	5 x Caterpillar 3516C HD 1603KW/1200rpm	
Build Yard	Far East Livingston shipyard	AC-Generator	5 x CAT SR4B 1530KW/1200rpm	
Hull Length	83.8m/275ft			
Hull Width	69.5m/228ft	Deck Cranes		
Displacement at	25585lt	Cranes Type	TSC PATRIOT	TSC PATRIOT
Loadline			PC198-200	PC198-201
Light Ship	12471.57lt	Main Hook	50t/49.2ft	50t/49.2ft
Accommodation	130	Auxiliary Hook	12t/11.8ft	12t/11.8ft
Operational Capabilities		Boom Length	Boom Length	120ft
Max. Designed	610m/2000ft	Cranes Type	TSC PATRIOT PC198-202	
Min. Designed	60.9m/200ft	Main Hook	70t/68.9ft	
Rated Drilling Depth	7620m/25000ft 5"DP	Auxiliary Hook	12t/11.8ft	
Drilling Equipment		Boom Length	80ft	
Drawworks	EMSCO, C3-II , Rated input power 3000hp	Variable Loading		
	PYRAMID,DYNAMIC MAST 186.5ft,	Transit VL	1900 lt	
Derrick/Mast	maximum static hook load	Drilling VL	3200lt	
	1000000lbs			
Top Drive	VARCO/TDS-4S 650t	Survival VL	3150 lt	
Pumps	3 x EMSCO FB1600			