



# JACK UP KANTAN 6

Jack Up - 375 ft



General		Operational Capabilities	
Name	KANTAN 6	Max Designed	114.3m(375ft)
Rig Type	Cantilever Jack Up	Min Designed	Site assessment
Design	Baker Marine Pacific Class 375	Rated Drilling Depth	9144m(30000ft) 5-1/2"DP
Year of build	2010	BOP Equipment	
Registry	China	BOP Stacks	1 x NOV Shaffer 10000psi 18-3/4" Bigboy 2 x NOV Shaffer 15000psi 18-3/4" 18-15M SLX
Classification	ABS/CCS	Power Equipment	
Build Yard	PPL Shipyard Pte Ltd - Singapore	Diesel Engines	5xCaterpillar3516CHD 1603KW/1200rpm
Hull Length	72.1m(236.56ft)	AC-Generator	5x KATO /6P63300 1720KW/1200rpm
Hull Width	68.4m(224.41ft)	Deck Cranes	
Hull Depth	8.5m(27.89ft)	Cranes Type	1 x BMC 900E      2x BMC 2250E
Max Displacement	19915.91mt	Main Hook	22.67m/6.1m      50.77m/7.5ft
Num of Leg/length	3 x154.3m(506.2ft)	Auxiliary Hook	5.0mt      10mt
Accommodation	120	Boom Length	100ft      120ft
Drilling Equipment		Variable Loading	
Drawworks	3xNOV ADS-10T, Rated input power 1150hp Intermittent duty1400hp	Transit VL	2268mt
Derrick/Mast	NOV D-170 40-2000-JU-BN,160ft, Maximum static hook load 1600kips	Drilling VL	3401mt
Top Drive	NOV/TDS-8SA 680mt	Survival VL	2948mt
Pump	3x NOV 14-P-220		



# JACK UP CPOE



JACK UP CPOE 10



JACK UP CPOE 7



JACK UP CPOE 11



JACK UP CPOE 19